

CORONA TRE 450


Corona diamantata saldata al laser, top di gamma per uso ad acqua su carotatrici a colonna con innesto al motore di 1"1/4 maschio. La spirallatura consente di velocizzare sensibilmente il tempo di foratura, agevolando la fuoriuscita dalla sede del foro del materiale d'asporto che tende a farla bloccare durante l'utilizzo. È l'ideale per gli utenti professionali che non vogliono sorprese sul cantiere e che ricercano sempre il massimo delle prestazioni. Su richiesta è possibile realizzare la riguarnitura delle corone, ma esclusivamente con sistema di saldobrasatura.

Diamond core bit laser welded, at the top of the range for wet use on column drilling machines with 1" 1/4 M motor fitting. The spiralling allows for the speeding up of drilling time by easing the exit of excess material from the hole which tends to block during use. Ideal for professional users who do not want surprises on site and who are always looking for excellent performance. It is possible to carry out re-tipping of segments on request, but only with silver-brazed welding system.


ACCIAIO SPIRALATO



PER USO
AD ACQUA








ATTACCO
1"1/4 F



LUNGHEZZA
450 MM

TABELLA TECNICA *Technical Spec*

cemento stagionato, laterizi, tegole, calcestruzzo armato <i>concrete, bricks, roof tiles, reinforced concrete</i>		SUPER
		OTTIMO
refrattari, graniti, pietre naturali, porfidi, arenaria, piastre ghiaino <i>refractory, granites, natural stone, porphyries, sandstone, aggregated concrete</i>		BUONO
		MEDIO
monocottura, bicottura, cemento fresco, asfalto <i>single fired tiles, double fired tiles, green concrete, asphalt</i>		SUFFICIENTE
marmi, gres porcellanato, klinker <i>marble, porcelain tiles, klinker</i>		INADATTO

COD.	Ø	SEGMENTI Segments	ALTEZZA Height
CLS45012A14*	12	COR.	8,00
CLS45014A14*	14	COR.	8,00
CLS45016A14*	16	COR.	8,00
CLS45018A14*	18	COR.	8,00
CLS45020A14*	20	COR.	8,00
CLS45022A14*	22	COR.	8,00
CLS45024A14*	24	COR.	8,00
CLS45026A14*	26	COR.	8,00
CLS45028A14*	28	COR.	8,00
CLS45030A14*	30	COR.	8,00
CLS45031A14*	31	4	8,00
CLS45035A14*	35	4	8,00
CLS45041A14*	41	5	8,00
CLS45045A14*	45	5	8,00
CLS45051A14*	51	5	8,00
CLS45056A14	56	5	8,00
CLS45061A14	61	6	8,00
CLS45066A14	66	6	8,00
CLS45071A14	71	7	8,00
CLS45076A14	76	7	8,00
CLS45081A14	81	8	8,00
CLS45086A14	86	8	8,00
CLS45091A14	91	9	8,00
CLS45101A14	101	10	8,00
CLS45107A14	107	10	8,00
CLS45111A14	111	11	8,00
CLS45121A14	121	11	8,00
CLS45127A14	127	12	8,00
CLS45131A14	131	13	8,00
CLS45141A14	141	13	8,00
CLS45151A14	151	13	8,00
CLS45161A14	161	13	8,00
CLS45171A14	171	13	8,00
CLS45181A14	181	14	8,00
CLS45205A14	205	15	8,00
CLS45225A14	225	16	8,00
CLS45250A14	250	17	8,00
CLS45300A14	300	21	8,00
CLS45350A14	350	23	8,00
CLS45400A14	400	25	8,00
CLS45450A14	450	29	8,00
CLS45500A14	500	33	8,00
CLS45600A14	600	37	8,00
CLS45700A14	700	43	8,00

* Dal ø 12 al ø 51 disponibile anche con attacco 1/2 gas / ø from 12 to 51 are available also with fitting 1/2 gas